

D20 4G LTE USB WiFi Dongle



Yifan Industry Co., Ltd

Unit1403, A06 Area, 3rd Software Park,
Jimei District, Xiamen, Fujian, China

Tel:+86 592 6101492

Fax:+86 592 5222813

Email: admin@yifanwireless.com

1. Overview

Yeacomm D20 is a high-speed USB Wi-Fi modem router. It is a multi-mode wireless terminal.

The D20 supports the following standards:

- ✧ Wireless access is available on both 3G&4G network.
- ✧ Internet connection sharing, up to 8 users can access the Wi-Fi network at the same time.
- ✧ Work with external power supply, no limited working time.
- ✧ CAT4 150 Mbps DL / 50 Mbps UL speed.
- ✧ Standard USB 2.0 compatible Tablet, Laptop, notebook, power bank, car&phone charging.
- ✧ One-touch connection.

2. Appearance:



2.Detail Specification

Basic Product Information	Description	Remark
Model	D20	4G Wi-Fi dongle
Frequency	European/African version	LTE:B1/B3/B5/B7/B8/B20/ B38/B40/B41 (120Mhz) WCDMA:B1/B8
	American version	LTE:B2/B4/B5/B7/B8/B28A /B28B/B66 WCDMA:B2/B4/B5/B8
Speed	TDD-LTE	150Mbps DL/50Mbps UL
	FDD-LTE	150Mbps DL/50Mbps UL
	UMTS/WCDMA/HSPA/HSPA+	21Mbps DL/5.76Mbps UL
Wi-Fi	2.4GHz, 802.11b/g/n up to 150Mbps	Modes supported: 802.11b mode 802.11g only mode 802.11n only mode 802.11b/g only mode 802.11b/g/n mode 802.11n 1*1(2.4GHz, 20MHz)
User amount	Max to 8 users	
AP Features	Security modes	Open WEP WPA-PSK WPA2-PSK WPA-WPA2 Hybrid mode(Mixed Mode) TKIP-CCMP Hybrid mode(Mixed Mode) WPS 2.0 Hidden SSID supported
	Concurrency (FC quality for LE1.0)	AP-STA mSSID (AP-AP) – up to 2 SSID's STA-STA communication block/allow between two SSIDs Independent security modes

		(Open, WEP, WPA, WPA2, WAPI) for concurrency modes above except WEP in both interfaces Channel of operation - same channel
	Other	QoS and PS WMM WMM-PS/uAPSD ERP protection Coexistence LTE coexistence (static channel selection) Data Switching/Forwarding Switching of packets amongst clients Support for forwarding data to and from WAN VPN Pass-through
❖ Interface		
Antenna	4G/3G/2G Main antenna 4G MIMO/3G Rx Diversity antenna WiFi antenna	Internal
USB	Standard USB 2.0	USB 2.0 High Speed
SIM/USIM Card slot	Yes	Standard 6 PIN SIM card interface, compliant with 3GPP 31.101 and 31.102
L*H*W(mm)	98mm * 28mm* 10mm	
Weight(g)	27g	
❖ LTE		
Power	Red	
Wi-Fi	Green	
LTE	Blue	
❖ Other Description		
RF Power Spec	Class 4 for UMTS/HSPA/LTE; Class 4 for GSM 850/900; Class 1 for GSM 1800/1900; Class E2 for EDGE 850/900/1800/1900	
Power Supply Input	USB 2.0 5V-1A	

❖ Software		
UI	WEB UI	
Operation system	Windows / Mac OS /IOS/ Android	
Operation	Internet Explorer/Mozilla Firefox/Google Chrome/Safari	
❖ Environmental		
Normal Operation	0°C to +45°C	
Restricted Operation	-10°C to +55°C	
Storage	-20°C to +70°C	
❖ Certificate		
ROHS	Compliance	
CE	Compliance	

Selection and Ordering Data

D20 Series modem

Model No.	Description
D20	4G LTE WIFI Modem
D20-N	4G LTE modem(without WIFI)