

## Yeacomm YF-S12 4g LTE indoor VoLTE VOIP CPE



**Yifan Industry Co., Ltd**

1403, A-06 Building, No.370, Chengyi  
Street, Jimei District, Xiamen, China

Tel:+86 592 6101492

Fax:+86 592 5222813

Email: [admin@yifanwireless.com](mailto:admin@yifanwireless.com)

## 1. Overview

As a high-performance LTE CPE device, the Yeacomm S12 enables home office (SOHO) users to get access to wireless and wired networks

The Yeacomm YF-S12 can work in any of the following network standards:

- Frequency Division Duplex (FDD)
- Time Division Duplex(TDD)
- Dual Carrier High Speed Packet Access Plus (DC-HSPA+)
- High Speed Packet Access Plus (HSPA+)
- High Speed Uplink Packet Access (HSUPA)
- High Speed Downlink Packet Access (HSDPA)
- Universal Mobile Telecommunications System (UMTS)
- Enhanced Data Rates for Global Evolution (EDGE)
- General Packet Radio Service (GPRS)
- Global System for Mobile Communications (GSM)

The Yeacomm YF-S12 provides the following services and functions :

- Data services
- Voice services (Optional)
- Short message service (SMS)
- Security functions
- Maintenance and management

**Yeacomm YF-S12 Pictures :**



## **2. Main functions:**

- \*Support 2G/3G/4G network connection
- \*VOLTE(optional)
- \*VoIP(optional)
- \*Support external antenna and build-in battery (Optional)
- \*WLAN function, easy to expand wireless network.
- \*Prevent loiter network, multi wireless safety ensuring.
- \*IP broadband band control, ensure the speed.
- \*Support network traffic statistics.
- \*Support up to 32 WIFI devices online simultaneously.
- \*IEEE802.11b/g/n
- \*Functioning as a Dynamic Host Configuration Protocol (DHCP) server and supporting
- \*Network Address Translation (NAT)
- \*Internet Protocol version 6 (IPv6)/Internet Protocol version 4 (IPv4) dual stack
- \*Security functions
- \* Wi-Fi protected setup (WPS)

### 3. Technical Specifications

#### 3.1 Hardware specifications

Item	Description	
Chipset	ZX297520V3E/ ZTE	
Memory	ROM: 128MB NAND Flash	
	RAM: 64MB DDR (128MB if Voice required)	
Technical standards	WAN: LTE/DC-HSPA+/HSPA+/HSPA/UMTS/EDGE/GPRS/GSM	
	WLAN: 802.11b/g/n	
Working bands	Version 1; B1/2/3/4/5/7/8/28 TDD: Band38/39/40/41 WCDMA:850/900/1900/2100Mhz GSM:850/900/1800/1900mhz	
	Version 2; B1/2/3/4/5/7/8/20 TDD: Band38/39/40/41 WCDMA:850/900/1900/2100Mhz GSM:850/900/1800/1900mhz	
Speed	FDD – LTE: 150Mbps/DL, 50Mbps/UL TDD-LTE: 150Mbps/DL, 50Mbps/UL HSPA+: 42Mbps/DL 5.76Mbps/UL HSUPA: 5.76Mbps (upload speed)/ HSDPA:7.2Mbps(download speed:) UMTS:384Kbps (download speed/upload speed)	
Wifi	WIFI Standard	IEEE 802.11b/g/n
	WIFI Rate	Highest rate 300 Mbps
	RF power	17dBm(Max) in 11b mode 17dBm(Max) in 11g mode 16dBm(Max) in 11n mode/chain
	Wifi users	Max up to 32 users
	CSFB	Support

External Port	4*RJ45 port (4* Lan)	
	1*RJ11(optional)	
	2*SMA external antenna port	
	1*sim card slot	
Buttons	One power button	
	One WPS button	
	One WIFI button	
	One Reset button	
Antenna	External antenna, Gain>5db	
Size	180*132*48mm	
Weight	320g	
PSU	12V/1A	
power	9-18V	
lights	power, network, signal, LAN	
Temperature	Working temperature	-20~50°C
	Storage temperature	40~85°C

### 3.2 Software Specification

Language	English/Chinese/Could be customized	
NAT	Supports NAT and Network Address and Port Translation (NAPT)	
	Supports fragmented message identification during common NAT	
DHCP Server	Enables and disables the DHCP server	
	Configures DHCP server address pools	
	Sets the lease time.	
	Displays the status of the DHCP server address pools, including host names, Media Access Control (MAC) addresses, IP addresses, and remaining lease time	
Firewall	Enables and disables the firewall.	
	Filters LAN MAC addresses	
	Filters LAN IP addresses.	
	Filters URLs.	
	Supports port Mapping	
	Supports demilitarized zone (DMZ).	
	Supports Universal Plug and Play (UPnP).	
	Speed limit	
IPv4v6 dual stack	Support IPV4, IPV6, IPV4V6	

Multiple APN	3
Cell lock	Support
Carrier SIM Lock	Support
SMS	Read, write, send SMS
MAC address authentication	Supports the MAC address authentication whitelist.
	Supports the MAC address authentication blacklist.
TR069	Support
VPN	Support L2TP VPN
Frequency locking	Support
Working mode	3g/4g
	3g only
	4g only
Remote upgrade	Support

#### 4.Packing List

Item	Quantity
4g mobile CPE Router	1
7.4V/2000Mah Rechargeable Battery (Optional)	1
RJ45 Cable	1
Power adapter	1
External antenna	2